Model 20 "Power House II"

Outstanding Power and Versatility





Model 20 Specs

Engine	Hatz Diesel
Rating	20 HP
Engine Torque	36.8 ft-lbs @ 2100
Max Rated Speed	3,000 RPM
Transmission	#14 3 Speed

Gear	Ratio
1st gear	3.12:1
2nd gear	1.86:1
3rd gear	1.0:1
Rev	3.75:1
Gear Box	Fairfield S1B
Final Reduction	31:1

Torque Requirements

Gear	Ratio Max.	Speed
1st gear	3,554 ft-lbs	31 RPM
2nd gear	2,121 ft-lbs	52 RPM
3rd gear	1,140 ft-lbs	97 RPM
Rev	4,278 ft-lbs	26 RPM

Hydraulic System

Thrust (norm	nal)	44,000 lbs	
Thrust (intermi	ttent)	51,000 lbs	
Hydraulic Pu	ımp	Gear Pump	
Pump Press	ure	4,400 psi	
Thrust Cylinders	(Three) 2-1/2	2" Bore x 36" Stroke	

Machine Data

Working Range	4" to 20" Casing Diameter
Hex Drive	2-1/4" hex
Push Bar	Manual

Dimensions

Length	84″
Width	26″
Height	34″
Centerline	13-3/4″
Master Track Length	9′
Extension Track Length	9′

Weight

	_
Machine	1,740 lbs
Track	240 lbs